

## **Match Point Aluminum System**

### **VB6000 (VB6000NS) Match Point Aluminum Stationary Competition Volleyball System**

#### **Applies Also to VB60, VB600, VB6002, VB6002NS**

System shall consist of the following components: Posts shall be constructed of a special 3½" OD 6063-T6 aluminum extrusion with a net adjusting track running the full length of the pole to facilitate infinite adjustment from tennis height (42") to men's competition volleyball (7' 11 5/8"). Height adjustment shall be accomplished by a single locking lever on each post. Top net rope shall be tightened using a worm gear style winch with a 2" wide nylon strap. Aluminum pole shall have a gold anodized finish. Top and bottom of pole shall be fitted with plastic floor protective inserts. Posts shall carry a 10-year limited warranty. Floor sockets (excluded on VB6000NS) shall consist of an aluminum socket assembly and a hinged bronze floor plate assembly. Floor socket adapters include: VB335 (3½" to 3"), VB340 (4" to 3"), VB354 (4" to 3½"). For socket depth adapter order VBDSS. The net shall be one meter high, be constructed of black polypropylene 3.5mm knotless woven webbing, have a Kevlar top rope and polypropylene bottom rope. For replacement net order VB1250K. Bottom rope and net side tapes shall be tightened by means of ratcheting style tensioners. or replacement Ratchet Net Tensioning Kit order VB1200RR. Padding for posts shall conform to all NCAA and National Federation of State High School Associations rules and be available in 12 school colors. For replacement padding order VB51P. Material is 1½" thick high-density foam with a heavy vinyl cover. Antennas shall conform to all applicable rules. For replacement antennas order VB13. Entire system shall weight 155#.

**VB6050 (VB6050NS) Recreational Aluminum Stationary Volleyball/Tennis Package**

System shall consist of the following components: Posts shall be constructed of a special 3 ½" OD 6063-T6 aluminum extrusion with a net adjusting track running the full length of the pole to facilitate infinite adjustment from tennis height (42") to men's competition volleyball (7' 11 5/8"). Height adjustment shall be accomplished by a single locking lever on each post. Top net rope shall be tightened using a worm gear style winch with a 2" wide nylon strap. Bottom rope and net shall be tightened by means of ratcheting style tensioners. Aluminum pole shall have a gold anodized finish. Top and bottom of pole shall be fitted with plastic floor protective inserts. Posts shall carry a 10-year limited warranty. Floor sockets (excluded in VB6050NS) shall consist of an aluminum socket assembly and an aluminum socket cap. The net shall be one meter high, be constructed of black polypropylene 3.5mm knotless woven webbing, have a Kevlar top rope and polypropylene bottom rope. Entire system shall weigh 145#.